

Philips
Composite A/V cable

6 ft

SWV2212W



Ensure a reliable connection

with this composite A/V cable

Depend on this cable to provide you with a reliable audio/video connection between components.

Enjoy good picture and sound quality

- High purity copper conductor for reliable signal transfer
- Nickel-plated connectors for reliable contact

Protects against signal loss

- Bare copper shielding

Easy installation

- Color coded connectors for instant recognition
- Non-slip ergonomic grip for easy use

Enjoy extended durability

- Molded plug for secure connections
- Flexible PVC jacket
- Rubber strain relief

PHILIPS
sense and simplicity

Composite A/V cable
6 ft

Specifications

Packaging dimensions

- **Packaging dimensions (W x H x D):**
3.75 x 7.75 x 1.5 inch
- **Nett weight:** .238 lb
- **Gross weight:** .273 lb
- **Tare weight:** .035 lb

Outer Carton

- **Outer carton (L x W x H):**
13.375 x 8.9 x 14.1 inch

- **Nett weight:** 5.714 lb
- **Gross weight:** 8.466 lb
- **Tare weight:** 2.752 lb

Inner Carton

- **Inner carton (L x W x H):** 8.3 x 4.125 x 6.5 inch
- **Nett weight:** .952 lb
- **Gross weight:** 1.248 lb
- **Tare weight:** .296 lb

SWV2212W/27

Product highlights

High purity copper

This copper conductor provides high accuracy in signal transfer with minimal resistance.

Nickel-plated connectors

Nickel-plated connectors establish a clean contact between the cable and connector for a reliable connection.

Bare copper shielding

Bare copper shielding protects against signal loss.

Color-coded connectors

Color coded connections make it easy to install your cable into the correct inputs and outputs

Easy grip

This non-slip grip makes connecting your components easy and ergonomically comfortable.

Molded plug

Molded plugs ensure secure connections between components and offer extended durability.

Flexible PVC Jacket

Flexible PVC jacket provided protection to the delicate core of the cable. It also offers extended durability and ease of installation.

Rubber strain relief

Rubber strain relief provides a secure, yet flexible juncture between the cable and the plug.



Issue date 2008-08-19

Version: 1.1.11

12 NC: 8670 000 37317
UPC: 6 09585 15165 9

© 2008 Koninklijke Philips Electronics N.V.
All Rights reserved.

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com